



山东路得威工程机械制造有限公司

SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.

High-Tech Zone Jining Shandong China. TEL:86-537-2239258 FAX:86-537-5160603 E-mail: roadway04@163.com

Automatic Curb Paver RWHM41



1. With great function controller, automatic calculation, suitable for kinds of projects




2. With imported brand CUMMINS diesel engine



3. With imported Danfoss hydraulic variable plunger pump, drives machine in stepless speed




4. With U.S.A hydraforce brand hydraulic control valve, to control each function intelligently




5. With hydraulic rod, high frequency and strong power



6. The crawler walking mechanism with automatic tension cylinder to increase the life of crawler



7. With patented steering system, flexible and convenient



8. With kinds of walking modes and can quickly switchover



9. With pressure monitors for each work mechanism to supervise in real time





山东路得威工程机械制造有限公司


SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.

High-Tech Zone Jining Shandong China. TEL:86-537-2239258 FAX:86-537-5160603 E-mail: roadway04@163.com

10. The mold is hanging, and dismantle hydraulically, labor saving



11. With hydraulic high pressure washing pump, can clean machine at any time



12. With Italy quick plugs to connect hydraulic power, smooth insertion and extraction, no oil leak





山东路得威工程机械制造有限公司

SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.

High-Tech Zone Jining Shandong China. TEL:86-537-2239258 FAX:86-537-5160603 E-mail: roadway04@163.com



Type	RWHM41
Engine	
Model	Cummins 4BTA 3.9
Type	Diesel Engine, liquid cooled, four cylinder
Power	97kW/2200rpm
Engine oil volume	9L
Traveling system	
Traveling mode	By crawler
Driving mode	By hydraulic
Steering mode	Collaborative/y\Yaw/Front wheel/Rear wheel/Automatic
Traveling speed	0-30m/min
Working speed	0-15m/min
Mold	
Mold traverse adjustment	1000mm
Mold height adjustment	400mm
Max. height of the mold	1300mm
Max. width of the mold	1300mm
Vibrating rod	
Hydraulic vibrating rod port	4
Volume	
Fuel tank volume	120L
Hydraulic tank volume	280L
Water tank volume	120L
Machine height adjustment	
Hydraulic height adjustment	980mm
Mechanical height adjustment	300mm
Dimension	
Transport size	6975x2500x3420mm
Weight	
Weight	11,700kg