

DATA SHEET:

VPON



| | | | |
|--|---|---|---|
| Description | 1 gang 1 way switch | 2 gang 1 way switch | 3 gang 1 way switch |
| Description | 1 gang 2 way switch | 2 gang 2 way switch | 3 gang 2 way switch |
| Description | 4 gang 1 way switch | 4 gang 2 way switch | |
| Description | 2 gang 1 way switch (with a common incoming line) | 3 gang 1 way switch (with a common incoming line) | 4 gang 1 way switch (with a common incoming line) |
| Dimensions(mm) | 86 * 86 | | |
| Material | PC & PA | | |
| Rated voltage(V) | 250 V | | |
| Rated current(A) | 16 AX | | |
| IP rating | IP 20 | | |
| Type of terminals | Screw - type | | |
| Type of conductor | Rigid/flexible | | |
| Smallest cross-sectional area (mm ²) | 1.5 | | |
| Largest cross-sectional area (mm ²) | 4.0 | | |
| Standard | IEC 60669-1:2017 | | |

FOSHAN VPON ELECTRIC CO.,LTD

(+86)-757-22127777 ; (+86)-757-22129999 ; (+86)-757-22177777

E-mail:sdnrq@qq.com ; Justin@manbang.net; Vicky@manbang.net

JIANGYI INDUSTRIAL AREA , LELIU TOWN , SHUNDE , FOSHAN , GUANGDONG , CHINA